



# DT600

TETRA DATA MODEM



[www.hytera.cn](http://www.hytera.cn)

Hytera Communications Corporation Limited

**HYT** is a registered trademark of Hytera

© 2010 Hytera, Co., Ltd. All Rights Reserved.

HYTERA retains right to change the product design and specification. Should any printing mistake occur, HYTERA doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

Address: HYT Tower, Hi-Tech Industrial Park North, Beihuan RD., Nanshan District, Shenzhen, China  
Tel : +86-755-2697 2999 Fax : +86-755-8613 7139 Post : 518057



3W power output

Standard PEI ,PPP/AT, interface

Dust & Water: IEC529 IP54

SDS Messages

Supporting GPS

User-friendly PC user interface

1.Dat(Data) indicator

2.Reg(Register) indicator

3.GPS working indicator

4.POWER indicator

5.ON/OFF button

6.GPS antenna interface

7.PEI interface

8.Power interface

9.Debugging interface

10.TETRA antenna interface



## Specification

### Basic Character

- ▶ Frequency Bands: 380-430MHz
- ▶ TX Output Power: 3W
- ▶ Receiver class A
- ▶ RF power control: 4 steps of 5 dB
- ▶ Sensitivity: -112dBm Static Sensitivity  
-103dBm Dynamic Sensitivity
- ▶ Transmission mode: TDMA
- ▶ Modulation: pi/4 DQPSK
- ▶ Channel Spacing: 25KHz
- ▶ Weight: <980g (including GPS Receiver)
- ▶ Dimensions: 194mm x133mm x 46mm (HxWxD)
- ▶ Power Input: 10.8V-15.6V (typical 13.2V)

### LED display

- ▶ DAT (Green), REG (Green), GPS signal (Green), Power (Red)

### Interface

- ▶ PEI requirement protocol : RS-232C
- ▶ AT & PPP : 2400~115200bps
- ▶ RS-232C
- ▶ Power supply connector
- ▶ Power On/Off button
- ▶ TETRA antenna connector, BNC female, 50 ohm
- ▶ GPS antenna connector, SMA female, 50 ohm

### Environmental

- ▶ Dust & Water: IEC529 IP54
- ▶ Operating Temp: -30 to +70° C
- ▶ Storage Temp: -40 to +85° C
- ▶ Operating Humidity: 0% to 100%

### GPS Receiver (option)

- ▶ Inbuilt GPS receiver
- ▶ GPS protocols for NEMA
- ▶ -142dBm acquisition sensitivity
- ▶ -158dBm tracking sensitivity
- ▶ location time is less than 2mins
- ▶ Accuracy:5 meters (50%),10 meters (95%)

### Data Services:

- ▶ Status Messages
- ▶ SDS Messages
- ▶ Circuit Mode Data- Data Rate: 7.2kbps ★
- ▶ Packet Data: Single slot Packet Data ★
- ▶ At-command interface for applications
- ▶ DNP3

### Security

- ▶ Authentication
- ▶ Encryption Algorithms TEA1,TEA3,TEA4
- ▶ SwMI Authentication of MS
- ▶ PIN/PUK code Access
- ▶ Security Class(Clear / SCK)
- ▶ Temporary disable/enable(stun)★
- ▶ Permanent disable (kill)★

### Accessories

- ▶ Power cable
- ▶ RS-232C data cable
- ▶ TETRA antenna (Optional)
- ▶ GPS antenna (GPS Module) (Optional)

(Due to continuous technology development, functions with a ★ mark contained in this brochure will be available to future versions of DT600.)